

# Toby Floor Polish



## Timber Floor Polish

### Description

Toby Floor Polish is a durable polish designed to enhance the life of timber floors finished with Toby oil based products such as Toby Tung Oil and Toby Oil Modified Urethane. It produces a sacrificial, clear finish resistant to traffic scuffing. When used regularly it maintains the timber floor's new look.

### Special features

- Provides a sacrificial protective coating for floors finished with Toby Tung Oil or Toby Oil Modified Urethane
- Easy to apply
- Adds years to the life of floors
- Returns floor's 'new' look
- Available in gloss and satin

### Properties

<b>Appearance:</b>	Milky white liquid
<b>Finish:</b>	Gloss and satin
<b>Density:</b>	1.04 g/ml
<b>Viscosity:</b>	13 seconds (Ford #4 cup)
<b>Packaging:</b>	1 litre plastic bottle 5 litre plastic bottle
<b>Flammability:</b>	Non-flammable
<b>Shelf life:</b>	12 months in unopened can (correctly stored)

### Directions for use

#### Surface preparation

#### New Floors coated with Toby Tung Oil or Toby Oil Modified Urethane:

Allow at least 7 days for the coating to fully cure. Ensure surface is free of contaminants. It may be necessary to damp mop the floor using Toby Polyclean as per label instructions, then apply Toby Floor Polish as per application instructions.

#### Existing Floors:

Ensure surface is free of contaminants. Use Toby Floor Stripper as per label instructions to remove old polish or wax. Damp mop the floor using Toby Polyclean as per label instructions, then apply Toby Floor Polish as per application instructions.

### Application

- Apply 2-3 thin coats of Toby Floor Polish using a premium grade cotton mop. Remove any fluff from mop prior to use
- Allow sufficient drying time between coats, approximately 1 hour
- For full gloss effect, burnish final coat (ensure sufficient drying time has been allowed) at 1000 rpm or greater if burnisher available

**Coverage:** 50 - 80 m<sup>2</sup>/litre

**Clean up:** Water

**Storage:** Protect from extremes of temperature. Store between 5°C and 30°C

### Care and maintenance

To extend the life of the floor, use floor-glides under chair and furniture legs and follow a regular maintenance programme along the following lines.

#### Daily

Sweep the floor daily with an electrostatic mop. Spot mop any spillages using Toby Polyclean.

#### Weekly

Floor should be damp mopped using Toby Polyclean. Burnish floor for full gloss effect.

(In high traffic/commercial environments it may be desirable to polish weekly to fortnightly).

#### Monthly to Quarterly

Wash floor with Toby Polyclean. Apply two coats of Toby Floor Polish as per instructions.

#### Annual Maintenance

Wash and strip the floor with Toby Floor Stripper. Apply two fresh coats of Toby Floor Polish.

#### Periodic Maintenance

Depending on traffic wear, wash and strip using Toby Floor Stripper. Sand floor with 150 grit screenback, use steel wool for edges. Thoroughly vacuum the floor to remove all dust then apply one coat of Toby Tung Oil or Oil Modified Urethane (whichever was used originally) as per label instructions, then apply Toby Floor Polish as per above instructions.

**Note:** In low traffic domestic environments floors will only need stripping and polishing as per the above procedure every 2-3 years.

